Detailed Specifications & Technical Data

METRIC MEASUREMENT VERSION



9930 Hook-up/Lead - UL AWM Style 1007

For more Information please call

1-800-Belden1



General Description:

Tinned copper conductor, PVC insulation. Rated 80°C, 300V. Rated 600V peak for electronic circuits, and internal wiring of electronic and electrical equipment.

Physical Characteristics (Overall)

Conductor

AWG:

# Conductors	AWG	Stranding	Conductor Material
1	30	7x38	TC - Tinned Copper

Total Number of Conductors:

Insulation

Insulation Material:

Insulation Material	Wall Thickness (mm)	Min. Avg. Wall (mm)
PVC - Polyvinyl Chloride	0.406	0.381

Overall Insulation

Overall Cable

Overall Nominal Diameter: 1.118 mm

Mechanical Characteristics (Overall)

Bulk Cable Weight: 1.786 Kg/Km

Applicable Specifications and Agency Compliance (Overall)

Applicable Standards & Environmental Programs

UL AWM Style:	UL Style 1007 (300 V 80°C)
UL Rating:	300 V RMS, 80°C
EU Directive 2011/65/EU (ROHS II):	Yes
EU CE Mark:	Yes
EU Directive 2000/53/EC (ELV):	Yes
EU Directive 2002/95/EC (RoHS):	Yes
EU RoHS Compliance Date (mm/dd/yyyy):	10/01/2005
EU Directive 2002/96/EC (WEEE):	Yes
EU Directive 2003/11/EC (BFR):	Yes
CA Prop 65 (CJ for Wire & Cable):	Yes
MII Order #39 (China RoHS):	Yes
ame Test	

UL Flame Test: VW-1

Plenum/Non-Plenum

Plenum (Y/N): No

Put Ups and Colors:

Item #	Putup	Ship Weight	Color	Notes	Item Desc
9930 0011000	1,000 FT	2.000 LB	BROWN	Р	30 STR PVC BRN
9930 002100	100 FT	0.200 LB	RED		30 STR PVC RED
9930 0021000	1,000 FT	2.000 LB	RED	Р	30 STR PVC RED
9930 003100	100 FT	0.200 LB	ORANGE		30 STR PVC ORG
9930 0041000	1,000 FT	2.000 LB	YELLOW	Р	30 STR PVC YEL
9930 005100	100 FT	0.200 LB	GREEN, DARK		30 STR PVC GRN
9930 0051000	1,000 FT	2.000 LB	GREEN, DARK	Р	30 STR PVC GRN
9930 007100	100 FT	0.200 LB	VIOLET		30 STR PVC VIO

Page 1 of 2

Detailed Specifications & Technical Data

METRIC MEASUREMENT VERSION



9930 Hook-up/Lead - UL AWM Style 1007

9930 008100	100 FT	0.200 LB	GRAY		30 STR PVC GRY
9930 009100	100 FT	0.200 LB	WHITE		30 STR PVC WHT
9930 0091000	1,000 FT	2.000 LB	WHITE	P	30 STR PVC WHT
9930 010100	100 FT	0.200 LB	BLACK		30 STR PVC BLK
9930 0101000	1,000 FT	2.000 LB	BLACK	Р	30 STR PVC BLK
9930 013100	100 FT	0.200 LB	BLUE, DARK		30 STR PVC DBLU
9930 0131000	1,000 FT	2.000 LB	BLUE, DARK	Р	30 STR PVC DBLU

Notes:

P = STRIPE COLORS ON STOCK SOLID COLORS. STRIPING ADDER OF \$8.00/M' FOR1 OR 2 STRIPES. 10000' MINIMUM ORDER FOR COLOR COMBINATION.PUT-UP WILL BE SUBJECT TO TWO PIECES (+ OR -) 10% PER SPOOL

Revision Number: 2 Revision Date: 10-01-2008

© 2016 Belden, Inc All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with EU RoHS (Directive 2002/95/EC, 27-Jan-2003). Material manufactured prior to the compliance date may be in stock at Belden facilities and in our Distributor's inventory. The information provided in this Product Disclosure, is correct to the best of Belden's knowledge, information, and belief at the date of its belotication. The information provided in this Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.

product.

Belden declares this product to be in compliance with EU LVD (Low Voltage Directive 2014/35/EU).

Page 2 of 2