

Specification Sheet

Part Number: SNP101GHS0X2



Snapper Hose Clamp, 4.12"-4.72" Bundle Diameter, PA66GF13, Black, 25/pkg

Article Number	190-00053
Туре	SNP101
Color	Black (BK)
Features & Benefits	• Installation and removal can be five times faster than conventional clamps . • Heat stabilized material is suitable for high temperature applications. • Completely reusable . • Will not rust or corrode . • Safety engineered. • No protruding band or cluster. • Can be installed with hose in place . • One-hand installation for tight places.
Quantity Per	bag

_				_					
ν	r۸	Иı	ıct	11	20	cri	nt		٦n
	ıv	u	a U L	$\boldsymbol{\nu}$	63	u i	v	ı١	,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,

Snapper Hose Clamps are lightweight and corrosion-resistant. Manufactured from high-performance thermoplastic materials selected to work well in a variety of diverse environments. A quick ratchet closure provides for reduced assembly line time and allows for application after connection of the hose. Release is achieved by initiating opposed lateral movement of the ratchet ends. Heat stabilized materials are available for high-temperature, motor, and under-hood applications. Snappers are also stable in a wide variety of chemicals including salts, bases, alcohols, ethers, detergents, gasoline, lubricating oils, and greases. The Snapper is available in 32 standard sizes ranging from 1/4" to 4-1/2" ID. Snappers are manufactured in white polyacetal and black polyamide 6.6 glass filled impact modified heat stabilized material. Custom designed and different colored or shaped Snappers are available based upon applications and volume requirements.

Short Description

Snapper Hose Clamp, 4.12"-4.72" Bundle Diameter, PA66GF13, Black, 25/pkg

Global Part Name

SNP101-PA66GF13-BK

Fixation	Method
i izatioii	MELLION

Plug-in mounting

Variant

Closed

Wall Thickness WT (Imperial)

.099

Wall Thickness WT (Metric)

2.525

Material

Polyamide 6.6 glass filled impact modified heat stabilized (PA66GF13%)

Material Shortcut

PA66GF13

Flammability

UL 94 HB

UV Resistant (Yes/No)

No

Operating Temperature (Metric)	-40°F to +221°F (-40°C to +105°C)
ROHS Complaint	Yes
Package Quantity(Imperial)	25
Package Quantity (Metric)	25
Customs Number	3926909987

Contact Us RoHS/WEEE Compliance Disclaimer Terms and Conditions

 $[\]hbox{@}$ 2018 HellermannTyton. All rights reserved.