

Specification Sheet

Part Number: 170-03054



Braided Sleeving, Aluminum Laminated Fiberglass, .5" Dia, AL/GF, Silver, 250 ft/bulk reel

Article Number

170-03054

Type

BSHTTST12SRB

Color

Silver (SR)

Features & Benefits

- A layer of aluminum provides protection from chemicals, scraping, cuts and abrasion.
- Additional layer also provides insulation barrier for vulnerable wires and cables within high temperature environments.
- Cuts with ordinary scissors for fast, easy application.

Quantity Per

reel

Product Description

A tubular shaped sleeving product that combines the protection of bonded aluminum and fiberglass into a single solution that is able to deflect radiant heat away from sensitive components inside the tube.

Short Description

Braided Sleeving, Aluminum Laminated Fiberglass, .5" Dia, AL/GF, Silver, 250 ft/bulk reel

Global Part Name

BSHTTST12SRB-AL/GF-ML

Length L (Imperial)

250.0

Length L (Metric)

76.2

Bundle Diameter Min (Imperial)

0.1

Bundle Diameter Min (Metric)

2.54

Bundle Diameter Max (Imperial)

0.437

Bundle Diameter Max (Metric)

11.1

Diameter D (imperial)

0.5

Diameter D (metric)

12.7

Nominal Diameter (Imperial)

1/2

Nominal Diameter (Metric)

12.7

Wall Thickness WT (Imperial)

0.025

Wall Thickness WT (Metric)

0.64

Material

Glass Fiber (GF) Aluminum (AL)

Material Shortcut

AL GF

Flammability	Non-Flammable
Halogen free	Yes
Operating Temperature (Metric)	-76°F to +491°F (-60°C to +255°C)
Reach Complaint(Article 33)	Yes
ROHS Complaint	Yes
Package Quantity(Imperial)	250
Package Quantity (Metric)	76.20
Customs Number	7019901000
Weight (Metric)	2.90
Weight (Imperial)	6.375