THIS COPY IS PROVIDED ON A RESTRICTED BASIS AND IS NOT TO BE USED IN ANY WAY DETRIMENTAL TO THE INTERESTS OF PANDUIT CORP. PANDU I T **WEIGHT** PART NUMBER 1.52 LB/EACH FRH4512X4 (690g/EACH) NOTES: 1. SEE CURRENT CATALOG FOR ADDITIONAL PART SUFFIXES TO INDICATE COLOR AND/OR PACKAGE QUANTITY. 15.24 2. THE FIBERRUNNER 12x4 HORIZONTAL 45° ANGLE FITTING IS DESIGNED WITH A MINIMUM 2" (50.8) [387.0] BEND RADIUS TO PROTECT FIBER OPTIC CABLES. 3. DIMENSIONS IN PARENTHESES ARE IN METRIC. 16.06 [407.9] 4.22 [107.3] ENG. REF.: D37617BN_DC_FRH4512X4_01.prt CAD FILENAME/LAYERS FRH4512X4.pdf CORP TINLEY PARK, ILLINOIS FIBERRUNNER TING UNLESS OTHERWISE SPECIFIED, DIMENSIONAL TOLERANCES ARE: UNLESS OTHERWISE SPECIFIED, ALL DIMENSIONS ARE GIVEN IN E. REVISED GENERAL NOTES INCHES, THIRD ANGLE PROJECTION. $(.XX) \pm .03 (.8)$ ANGLES ± MAT'L: D. REVISED PART WEIGHT SCALE NONE C. REVISED CAD FILENAME JHNL DRAWING NO. B. REVISED DRAWING TITLE DWG ABS 1-29-06 DTP RN 37617-65 RN RN 12-29-00 A. REVISED AND REDRAWN 37617-65 DESCRIPTION GMBH REV DATE CHK ECN CUST SUP HIW