



#### General ordering data

Order No.	0479460000
Part designation	AST 4/35 SF 6.3
Version	Special terminal, special connections, 2.5 mm <sup>2</sup> , Screw connection, PA 66, beige, TS 35
EAN	4008190108625
Qty.	100 pc(s).

#### Product notes

Note, ordering data	Cable-lug connections should be connected with insulating sleeves. 20 A with F 6.3 or 2 x F 2.8
Note, technical data	The rated voltage is 800 V when using a cable-lug (flat) connector with IH 6.3 insulating sleeves.
Note, accessories	Pluggable adapter STA 2,5/2 - STA 2,5/8 only for PA - Version.

#### Additional technical data

Colour of insulating material	beige
Connection direction	on side
End plate required	Yes
Explosion-tested version "Ex e"	No
Installation advice	TS 35
Insulating material	PA 66
Levels cross-connected internally	No
No. of identical terminals	1
No. of levels	1
No. of terminal strips per level	2
Open sides	right
Operating temperature range	- 50 °C, + 100 °C
Product family	SAK Series
Type of connection	Screwed
Type of mounting	Snap-on
UL 94 flammability rating of insulation material	V2
Version	Feed-through terminal

#### CSA rating data

Voltage (CSA)	300 V
CSA current	16 A
Min. cross-section (CSA)	AWG 24
Max. cross-section (CSA)	AWG 12

#### Conductors for clamping (additional connection)

Type of connection	Flat-blade connection
No. of connections	1
Flexible with ferrule, min. (DIN 46228 pt 1)	0.5 mm <sup>2</sup>
Flexible with ferrule, max. (DIN 46228 pt 1)	2.5 mm <sup>2</sup>

#### Conductors for clamping (rated connection)

Clamping range, min.	0.2 mm <sup>2</sup>
Clamping range, max.	4 mm <sup>2</sup>
Type of connection	Screw connection
2nd type of connection	screwed
Connection direction	on side
No. of connections	1
Stripping length	9 mm
Clamping screw	M 2.5
Blade size	0.6 x 3.5 mm
Tightening torque range	0.4...0.7 Nm
Torque level with DMS electric screwdriver	1
Gauge to IEC 60947-1	A3
Solid, min.	0.5 mm <sup>2</sup>
Solid, max.	4 mm <sup>2</sup>
Stranded, min.	1.5 mm <sup>2</sup>
Stranded, max.	2.5 mm <sup>2</sup>
Flexible, min.	0.5 mm <sup>2</sup>
Flexible, max.	2.5 mm <sup>2</sup>
Flexible with ferrule, min. (DIN 46228/1)	0.5 mm <sup>2</sup>
Flexible with ferrule, max. (DIN 46228/1)	2.5 mm <sup>2</sup>
Flexible, min., ferrule with plastic collar (DIN 46228 pt 4)	2.5 mm <sup>2</sup>
Flexible, max., ferrule with plastic collar (DIN 46228 pt 4)	2.5 mm <sup>2</sup>
Twin wire-end ferrule, min.	0.5 mm <sup>2</sup>
Twin wire end ferrule, max.	1.5 mm <sup>2</sup>
AWG conductor size, min.	AWG 24
AWG conductor size, max.	AWG 12
AWG conductor size, min.	0.21 mm <sup>2</sup>
AWG conductor size, max.	3.31 mm <sup>2</sup>

#### Dimensions

Width	6.2 mm
Height of lowest version	40.1 mm
Length	40 mm
Weight	7.32 g
TS 35 offset	20 mm

#### Disconnect terminals

Torque level with DMS electric screwdriver	1
--	---

#### Other connections

Cable-lug connection	unslotted
No. of connections	1

#### Other connections

Rated cross-section spade connector 2.8 mm	1 mm <sup>2</sup>
Rated cross-section spade connector 6.3 mm	2.5 mm <sup>2</sup>

#### Rating data

Rated cross-section	2.5 mm <sup>2</sup>
Rated voltage	500 V
Rated impulse voltage	6 kV
Rated current	20 A
Standards	IEC 60947-7-1 / IEC 61210
Current with max. conductor	20 A
Pollution severity	3

#### UL rating data

Voltage (UL)	300 V
Current (UL)	13 A
Min. cross-section (UL)	AWG 22
Max. cross-section (UL)	AWG 12

#### Approvals

Approvals institutes



#### Classifications

ETIM 2.0	EC000897
ETIM 3.0	EC000897
eClass 4.1	27-14-11-31
eClass 5.0	27-14-11-31
eClass 5.1	27-14-11-31

#### Similar products

Order No.	Part designation	Version
0664860000	AST 1/35 6.3	Special terminal, special connections, 2.5 mm <sup>2</sup> , Flat-blade connection, PA 66, beige, TS 35
0699660000	AST 1/35 6.3/2.8	Special terminal, special connections, 2.5 mm <sup>2</sup> , Flat-blade connection, PA 66, beige, TS 35
0479360000	AST 3/35 6.3	Special terminal, special connections, 2.5 mm <sup>2</sup> , Flat-blade connection, Polyamide, beige, TS 35
0460360000	AST 3/35 6.3/2.8	Special terminal, special connections, 2.5 mm <sup>2</sup> , Flat-blade connection, Polyamide, beige, TS 35
0460460000	AST 4/35 SF 6.3/2.8	Special terminal, special connections, 2.5 mm <sup>2</sup> , Screw connection, Polyamide, beige, TS 35