

## **Specification Sheet**

Part Number: CT2012X2



Self-Laminating Tag, Caution Write-On, Telephone Cable, 3.5" x 2.0", Yellow, 25/pkg

| Article Number      | 597-00031   |
|---------------------|---|
| Туре                | CT2012  |
| Color               | Yellow (YE)   |
| Features & Benefits | <ul> <li>Clear laminating plastic flap permanently protects the writing and data<br/>marked on the tag.</li> <li>Mounting holes for easy mounting using standard cable<br/>ties.</li> <li>Markers can be mounted in any direction, either vertically, horizontally,<br/>as a wrap-around identification plate or as a flag for the best visual position on<br/>the cable assembly.</li> </ul> |
| Quantity Per        | pack  |

| Product Description   | HellermannTyton's Rite-On Markers are made from a flexible vinyl film and used to mark wire and cable. The self-laminating labels have a clear tail which seals the legend under clear vinyl, maintaining the quality of the labels. The Rite-On markers are packaged in a reusable dispenser made from high impact plastic which is resistant to oils and grease. boldProduct Features/bold - Easily and conveniently fits in a pants or shirt pocket Once loaded, unit allows minimal label exposure to dust and moisture Can be used with standard ball point pens or HellermannTyton nylon marking pens Excess liner is easily cut-off by tearing it over the edge guide at the front of the unit The dispenser can be reloaded over and over again, making it a cost-effective and efficient method of labeling. |
|-----------------------|---|
| Short Description     | Self-Laminating Tag, Caution Write-On, Telephone Cable, 3.5" x 2.0", Yellow, 25/pkg   |
| Global Part Name      | CT2012-PVC-YE   |
| Technical Description | Caution Write-On Self-Laminating Tag, Telephone Cable, 3.5" X 2.0", Yellow  |
|                       |   |
| Width W (Imperial)    | 3.5   |
| Width W (Metric)      | 88.9  |
| Height H (Imperial)   | 2.0   |
| Height H (Metric)     | 6.35  |
|                       |   |

| Material          | Polyvinylchloride (PVC) |
|-------------------|-------------------------|
| Material Shortcut | PVC                     |
| Adhesive          | Acrylic                 |

Halogen free

No

| Adhesive Operating Temperature | -40°F to +302°F (-40°C to +150°C) |
|--------------------------------|-----------------------------------|
| Operating Temperature (Metric) | -40°F to +257°F (-40°C to +125°C) |
| Reach Complaint(Article 33)    | Yes                               |
| ROHS Complaint                 | Yes                               |
| Package Quantity(Imperial)     | 25                                |
| Package Quantity (Metric)      | 25                                |
| Customs Number                 | 3919905060                        |
| Content Unit(BMEcat)           | pack                              |
| Labels per Column              | 1                                 |
| Labels per Row                 | 1                                 |
| Weight (Metric)                | 0.22                              |
| Weight (Imperial)              | 0.5                               |

Contact Us RoHS/WEEE Compliance Disclaimer Terms and Conditions

 $<sup>\</sup>hbox{@ 2018 HellermannTyton. All rights reserved.}$