

Specification Sheet

Part Number: 156-00282



Heavy-Duty Fir Tree Mount Cable Tie, 15" x .5"L, .03"-.28" Panel Thick, 50lb, PA66HIRHS, Black, 500/pkg

Article Number	156-00282
Type	T50LFT7
Color	Black (BK)
Features & Benefits	<ul style="list-style-type: none">• Friction tab inside of fir tree allows tie to sit in mount without falling out prior to installation.• Initial fir tree serves as a locating feature for assistance in blind assembly applications.• Disc feature provides anti-rattle protection in high vibration applications.
Quantity Per	bag

Product Description

Fir tree mounts with ties cables provide a secure grip in mounting holes and protect against dirt and other impurities. The mount provides low insertion and high extraction force, and slides along the cable tie for the proper orientation. This is sold as an assembly with the cable tie.

Short Description

Heavy-Duty Fir Tree Mount Cable Tie, 15" x .5"L, .03"-.28" Panel Thick, 50lb, PA66HIRHS, Black, 500/pkg

Global Part Name

T50LFT7-PA66HIRHS-BK

Minimum Tensile Strength (Imperial)

50.0

Minimum Tensile Strength (Metric)

225

Length L (Imperial)

15.0

Length L (Metric)

380.0

Fixation Method

Fir Tree

Identification Plate Position

none

Tie Closure

plastic pawl

Variant

Inside Serrated

Width W (Imperial)

0.18

Width W (Metric)

4.6

Bundle Diameter Min (Imperial)

0.16

Bundle Diameter Min (Metric)

4.0

Bundle Diameter Max (Imperial)

3.4

Bundle Diameter Max (Metric)

85.0

Height H (Imperial)	.78
Height H (Metric)	19.80
Panel Thickness Min(Imperial)	0.031
Panel Thickness Max(Imperial)	0.276
Panel Thickness Min (Metric)	0.8
Panel Thickness Max (Metric)	7.0
Mounting Hole Diameter D (Imperial)	0.26 - 0.28
Mounting Hole Diameter D (Metric)	6.5 - 7.0 mm
Mounting Hole Diameter D Min (Imperial)	0.24
Mounting Hole Diameter D Max (Imperial)	0.8
Mounting Hole Diameter D Max (Metric)	7.0
Disc Diameter(Metric)	21.6
Disc Diameter (Imperial)	0.9
Material	Polyamide 6.6, high impact modified, heat stabilized (PA66HIRHS)
Material Shortcut	PA66HIRHS
Material Cable Tie	Polyamide 6.6 heat stabilized (PA66HS)

Flammability

UL 94 HB

Operating Temperature (Metric)

-40°F to +230°F (-40°C to +110°C)

ROHS Complaint

Yes

Package Quantity(Imperial)

500

Package Quantity (Metric)

500

Customs Number

3926909987