

## Specification Sheet

Part Number: 111-85519



Push Mount Arrowhead Tie Wings, 4" Long, 18lb Tensile, PA66HS, Natural, 100/bag

<b>Article Number</b>	111-85519
<b>Type</b>	T18RSF
<b>Color</b>	Natural (NA)
<b>Features &amp; Benefits</b>	<ul style="list-style-type: none"><li>•Two piece assembly allows the mount to slide along the strap ensuring proper orientation.</li><li>•Arrowhead style mount provides low insertion and high extraction force.</li><li>•Arrowhead disc protects against dirt and other impurities.</li></ul>
<b>Quantity Per</b>	bag

### Product Description

Wing design helps stabilize the tie in high vibration applications. One-piece mounting ties offer a complete solution by both bundling cable and simultaneously providing a mounting solution. HellermannTyton's one-piece mounting ties offer the ideal combination of high specification materials and superior design to suit the mounting and bundling needs of complex applications.

<b>Short Description</b>	Push Mount Arrowhead Tie Wings, 4" Long, 18lb Tensile, PA66HS, Natural, 100/bag
<b>Global Part Name</b>	T18RSF-PA66HS-NA
<b>Minimum Tensile Strength (Imperial)</b>	18.0
<b>Minimum Tensile Strength (Metric)</b>	80
<b>Length L (Imperial)</b>	4.0
<b>Length L (Metric)</b>	100
<b>Fixation Method</b>	Arrowhead
<b>Identification Plate Position</b>	none
<b>Releasable Closure</b>	No
<b>Tie Closure</b>	plastic pawl
<b>Variant</b>	Inside Serrated
<b>Width W (Imperial)</b>	0.1
<b>Width W (Metric)</b>	2.5
<b>Bundle Diameter Min (Imperial)</b>	0.06
<b>Bundle Diameter Min (Metric)</b>	1.5
<b>Bundle Diameter Max (Imperial)</b>	0.6

<b>Bundle Diameter Max (Metric)</b>	16.0
<b>Thickness T (Imperial)</b>	0.039
<b>Thickness T (Metric)</b>	1.0
<b>Panel Thickness Min(Imperial)</b>	0.031
<b>Panel Thickness Max(Imperial)</b>	0.12
<b>Panel Thickness Min (Metric)</b>	0.8
<b>Panel Thickness Max (Metric)</b>	3.0
<b>Mounting Hole Diameter D (Imperial)</b>	0.18 - 0.19
<b>Mounting Hole Diameter D (Metric)</b>	4.6 - 4.8 mm
<b>Mounting Hole Diameter D Min (Imperial)</b>	0.177
<b>Mounting Hole Diameter D Max (Imperial)</b>	0.19
<b>Mounting Hole Diameter D Max (Metric)</b>	4.85
<b>Material</b>	Polyamide 6.6 heat stabilized (PA66HS)
<b>Material Shortcut</b>	PA66HS
<b>Material Cable Tie</b>	Polyamide 6, heat stabilized (PA6HS)
<b>Operating Temperature (Metric)</b>	-40°F to +221°F (-40°C to +105°C)

<b>Reach Complaint(Article 33)</b>	Yes
<b>ROHS Complaint</b>	Yes
<b>Package Quantity(Imperial)</b>	100
<b>Package Quantity (Metric)</b>	100
<b>Customs Number</b>	3926909987
<b>Content Unit(BMEcat)</b>	pcs.
<b>Weight (Metric)</b>	0.3