



- NOTES:
1. MATERIAL: SEE TABLE
 2. FINISHES: SEE TABLE
 3. PRODUCT SPEC: PS-130299-001
 4. PACKAGING: PK-130299-001
 5. MATES WITH: MALE D-CODE CABLE ASSEMBLY
 6. ELECTRICAL SPECS:
VOLTAGE: 250V AC/DC
CURRENT: 4 AMPS
 7. PROTECTION: IP67
 8. ASSEMBLY IS RoHS COMPLIANT

ITEM	QTY.	DESCRIPTION	MATERIAL	FINISH
9	1	INSULATOR O-RING	VITON	BROWN
8	1	PANEL O-RING	VITON	RED
7	1	MATING O-RING	VITON	RED
6	A/R	POTTING COMPOUND	EPOXY	BLACK
5	1	PANEL NUT	ZINC (DIE-CAST)	CHROME/DUPLEX NICKEL
4	2	CONTACT SOCKET SHORT	BRASS	GOLD PLATED
3	2	CONTACT SOCKET, LONG	BRASS	GOLD PLATED
2	1	4/C D-CODE INSULATOR	PUR	BLACK
1	1	RECEPTACLE SHELL, M12	ZINC (DIE-CAST)	WHITE BRONZE PLATING

POTTING WAS RED
EC NO: IPG2017-0514
DRW:MBRZOWSKI 2016/11/21
CHKD:
APPR:APATEL 2016/12/05
REV

QUALITY SYMBOLS	GENERAL TOLERANCES (UNLESS SPECIFIED)
▽=0	mm INCH
▽=0	4 PLACES ± .13 ± .01
	3 PLACES ± .005 ± .005
	2 PLACES ± .01 ± .01
	1 PLACE ± .03 ± .03
	ANGULAR ± 2°

DIMENSION STYLE		SCALE		DESIGN UNITS		THIRD ANGLE PROJECTION	
IN/MM		3:1		INCH		THIRD ANGLE PROJECTION	
DRAWN BY	DATE	TITLE				MIC PCB RECEPTACLE 4C, D-CODE, 90 DEG	
RSTONE	2010/05/17	MATERIAL NO.				SD-130299-005	
CHECKED BY	DATE	DOCUMENT NO.				SHEET NO.	
K. JOZWIK	2010/05/25	SEE CHART				1 OF 1	
APPROVED BY	DATE	THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION					
JFMURPHY	2010/05/20						