REVISION HISTORY **ROHS COMPLIANT** PRODUCT DATA DRAWING DATE APPROVED DESCRIPTION REL. DCN 36862 06/23/09 STW .560 [14.22] COMPRESSED (.746 [18.95] COMPRESSED) .620 UNCOMPRESSED BMZ 75 OHM MALE PIN .031±.002 [0.79±0.05] MATE ONLY TO BMZ 75 OHM FEMALE- $\emptyset.3145\pm.0015$ [7.99 ±0.04] \emptyset .280 [7.11] -ACCEPTS RG-179 .511 [12.98] COMPRESSED CABLE OR EQUIVALENT

.571[13.66] UNCOMPRESSED

MATERIAL:

BODY & SLEEVE: STAINLESS STEEL PER AMS-5640,

ALLOY UNS S30300, TYPE 1

FERRULE

CRIMP RING: BRASS PER ASTM B16 ALLOY UNS No. 36000

CONTACT

LOCK RING: BERYLLIUM COPPER PER ASTM B196, ALLOY No. UNS C17300, TD04

PTFE PER ASTM D1710, TYPE I, GRADE 1, CLASS B **INSULATOR:**

SPRING: STAINLESS STEEL PER ASTM A313, TYPE 631.

FINISH:

BODY, SLEEVE

& SPRING: PASSIVATED PER AMS-2700, TYPE 2.

GOLD PER ASTM B488, TYPE II, CONTACT:

CODE C, CLASS 1.27; OVER NICKEL PER AMS-QQ-N-290, CLASS 1, .00005" MIN.

FERRULE, CRIMP RING AND LOCK RING: NICKEL PER AMS-QQ-N-290.

PERFORMANCE:

IMPEDANCE: 75 OHMS

FREQ. RANGE: 950 TO 2150 MHz **VSWR:** 1.5:1 950 TO 2150 MHz

INSERTION LOSS: .06 X SQRT(F(F IN GHz))

DWV: 1000 VRMS

OPERATING TEMP.: -55°C TO +125°C MATERIAL: SEE NOTES FINISH: **SEE NOTES** SURFACE AREA: N/A **PROPRIETARY** THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF SV MICROWAVE, INC. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF SV MICROWAVE, INC IS PROHIBITED.

I	DIMENSIONS ARE IN INCHES TOLERANCES:			
4	FRACTIONAL: ±1/64 ANGULAR: X° ±1°0' X°X' +15'			
	DECIMAL: X ±.030 .XX ±.010 .XXX ±.005			
4	INTERPRET DIMENSIONS AND TOLERANCES PER ASME Y14.5M - 1994			

.XXX ±.005	
INTERPRET DIMENSIONS AND TOLERANCES PER ASME Y14.5M - 1994	
THIRD ANGLE PROJECTION	
1	

UNLESS OTHERWISE SPECIFIED	
1) ALL DIMENSIONS ARE IN INCHES [MILLIMETERS] 2) ALL DIMENSIONS ARE AFTER PLATING. 3) BREAK CORNERS & EDGES .005 R. MAX. 4) CHAM. 1ST & LAST THREADS.	
63/	
E) CUIDEACE DOLICUINIECE V MIL CED 40	

5) SURFACE ROUGHNESS V MIL-STD-10.
6) DIA:'S ON COMMON CENTERS TO BE CONCENTRIC WITHIN .005 T.I.R.
7) REMOVE ALL BURRS

NGLE PROJECTION	DRAWN:	JMC 02/11/09
<u> </u>	CHECKED:	PS 02/11/09
	APPROVED:	PS 02/11/09

 $\emptyset.275^{+.001}_{-.002} \left[6.99^{+0.03}_{-0.05} \right]$

SV Microwave, Inc.

2400 Centrepark West Drive, Suite 100 West Palm Beach, FL 33409

TITLE: **BMZ 75 OHM SOCKET** FOR RG-179 CABLE FIT M38999 SIZE 8 CAVITY

SIZE B	95077	DWG. NO. SF9811-	60005
S	CALE: 6:1		SHEET 1 OF