

HOUSING: THERMOPLASTIC; COLOR: GREY WEDGELOCK: THERMOPLASTIC; COLOR: ORANGE SEALS: SILICONE RUBBER

CONTACTS: COPPER ALLOY; NICKEL PLATED

- 2. SPECIFICATIONS:
 - 2.1 CURRENT RATING: 25 AMPS
 - 2.2 OPERATING TEMPERATURE: -55°C TO +125°C
 - 2.3 DIELECTRIC WITHSTANDING VOLTAGE: LESS THAN 2 MILLIAMPS CURRENT LEAKAGE @ 1500 VOLTS AC.
 - 2.4 INSULATION RESISTANCE: 1000 MEGOHMS MIN @ 25°C.
 - 2.5 CONTACT MILLIVOLT DROP: 60 MILLIVOLT DROP @ 25 AMP TEST CURRENT.
 - 2.6 MOISTURE RESISTANCE: IP67 (MATED CONDITION)
 - 2.7 CONNECTOR MATING CYCLE DURABILITY: 100 CYCLES

- 4. AVAILABLE HAND CRIMPER: CA-5D12
- 5. ALL COMPONENTS ARE ROHS COMPLIANT.
- 6. ALL DIMENSIONS ARE FOR REFERENCE USE ONLY.

7\WIRE RANGE OF CONTACTS INCLUDED IN KIT: 12 - 14 AWG

 ${f/8ackslash}$ CONTACT SIZE AND REAR SEAL WIRE RANGE:

CONTACT	MIN. INSUL.	MAX. INSUL.	TYPICAL	
SIZE	O.D.	O.D.	WIRE RANGE	
12	3.40 mm (.134 in)	4.95 mm (.195 in)	10 - 14 AWG	

7\	4	AT62-203-12141			CONTACT, SOCKET, SOLID, SIZE 12, 12-14 AWG				3
	1 AWP-4S				S-WEDGELOCK, 4 POSITION, ATP SERIES			RIES	2
	1	ATP06-4S			PLUG, 4 POSITION, ATP SERIES 1				
	QUANTITY	QUANTITY PART NUMBER		2	DESCRIPTION				ITEM
		MATERIALS LIST							
	UNLESS OTHERWISE SPECIFIED		SIGNATURES		S DATE		mnho	nol	
	All dimensions are in metric(mm). Tolerances are as follows: PL DEC ±0.30 Fractions +1/64		DRAWN:	D.PARKS	10/SEP/13	Amphenol			
	2 PL DEC ±0.15 3 PL DEC ±0.08	Angles ±1°	CHECKED:			Sir	ne Systems - www.amphen	nol-sine.com	
	3) Note reference =X		ENGINEER:			44724 Morley Drive Clinton Township, MI 48036			
			APPROVAL:						
			CUSTOMER:		KIT, ATP SERIES, 4 POSITION PLUG,				
			THIS DRAWING IS SUPPLIED FOR INFORMATION ONLY, DESIGN FEATURES.		CONTACTS, AND WEDGELOCK				
PROCESS SPECIFICATIONS:			SPECIFICATIONS AND PERFORMANCE DATA SHOWN HEREON ARE THE PROPERTY OF THE AMPHENOL CORPORATION. NO RIGHTS OF REPRODUCTION ARE IMPULED. ALL DIMENSIONS ARE SILE ICT TO NORMAL		B C-	ATP06-4S-	KIT01	A	
	NEXT ASS'Y:		MANUFACTURING VARIATIONS.		SCALE: NONE		SHEET 1 OF	1	

REVISIONS