



Part Number: 9512

300V PLTC, (2 pr) 22 AWG (7x30) TC, PVC/PVC, Foil Shld, CMG

Request Sample

Product Description

Two 22 AWG pair stranded (7x30) tinned copper conductors, PVC insulation, overall Beldfoil® shield (100% coverage), PVC jacket.

Technical Specifications

Physical Characteristics (Overall)

Conductor AWG Stranding Material No. of Pairs 22 7x30 TC - Tinned Copper 2 Conductor Count: 4 Total Number of Pairs: 2 Total Number of Triads: N/A Conductor Size: 22 AWG

Insulation

| Material | Nominal Wall Thickness |
|--------------------------|------------------------|
| PVC - Polyvinyl Chloride | 0.017 in |

Color Chart

| Number | Color |
|--------|--------------------------|
| 1 | Black & Red and Numbered |
| 2 | Black & Red and Numbered |

Outer Shield Material

| Type | Material | Material Trade Name | Coverage [%] | Drainwire Material | Drainwire AWG | Drainwire Construction n x D |
|------|--------------------|---------------------|--------------|--------------------|---------------|------------------------------|
| Таре | Aluminum/Polyester | Beldfoil® | 100 % | TC - Tinned Copper | 22 | 7x30 mm |

Outer Jacket Material

| Material | Nominal Diameter | Nominal Wall Thickness | Ripcord |
|--------------------------|------------------|------------------------|---------|
| PVC - Polyvinyl Chloride | 0.295 in | 0.042 in | Yes |

Construction and Dimensions

Print Legend: LEGEND: BELDEN XXXX E34972 2PR22 SHIELDED (UL) CMG 105C OR PLTC OR ITC SUN RES DIR BUR OR AWM 2464 80C 300V OR C(UL)

Electrical Characteristics

Conductor DCR

| Nominal Conductor DCR | Nominal Outer Shield DCR |
|-----------------------|--------------------------|
| 15 Ohm/1000ft | 15 Ohm/1000ft |

Capacitance

| No | om. Capacitance Conductor to Conducto | Nom. Capacitance Conductor to Other Conductor to Shield |
|----|---------------------------------------|---|
| 26 | 3 pF/ft | 45 pF/ft |
| Sh | Shielding: Foil(s) or Copper Tape(s) | |

Inductance

Nominal Inductance

Voltage



Temperature Range

| UL Temp Rating: | 105°C |
|-----------------------|-----------------|
| Operating Temp Range: | -30°C To +105°C |

Mechanical Characteristics

| Bulk Cable Weight: | 37 lbs/1000ft |
|----------------------------------|---------------|
| Max Recommended Pulling Tension: | 20 lbs |
| Min Bend Radius/Minor Axis: | 3 in |

Standards

| NEC/(UL) Specification: | CMG, ITC-ER, PLTC-ER |
|--------------------------|----------------------|
| CEC/C(UL) Specification: | CMG |
| UL AWM Style: | 2464 |

Applicable Environmental and Other Programs

| EU Directive 2000/53/EC (ELV): | Yes |
|---------------------------------------|-------------------------------|
| EU Directive 2003/96/EC (BFR): | Yes |
| EU Directive 2011/65/EU (ROHS II): | Yes |
| EU Directive 2012/19/EU (WEEE): | Yes |
| EU Directive 2015/863/EU: | Yes |
| EU Directive Compliance: | EU Directive 2003/11/EC (BFR) |
| EU CE Mark: | Yes |
| EU RoHS Compliance Date (yyyy-mm-dd): | 2005-04-01 |
| CA Prop 65 (CJ for Wire & Cable): | Yes |
| MII Order #39 (China RoHS): | Yes |

Suitability

| Suitability - Burial: | Yes |
|------------------------------------|-----|
| Suitability - Indoor: | Yes |
| Suitability - Outdoor: | Yes |
| Suitability - Sunlight Resistance: | Yes |

Flammability, LS0H, Toxicity Testing

| C(UL) Flammability: | FT4 |
|---------------------|-------------------|
| UL Flammability: | UL1685 UL Loading |
| IEEE Flammability: | 1202 |
| UL voltage rating: | 300 V RMS |

Plenum/Non-Plenum

| Plenum (Y/N): | No |
|---------------|----|

Part Number

Variants

| Item # | Color | Footnote |
|--------------|--------|----------|
| 9512 0601000 | Chrome | С |
| 9512 060500 | Chrome | С |
| 9512 0605000 | Chrome | CZ |

| Footnote: | C - CRATE REEL PUT-UP. |
|-----------|--|
| Footnote: | Z - FINAL PUT-UP MAY VARY (= OR -) 10% FOR SPOOLS OR REELS AND (+ OR -) 5% FOR UNREEL CARTONS FROM LENGTH SHOWN. |

© 2018 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.