

COUNT	DESCRIPTION OF REVISIONS	BY	CHKD	DATE	COUNT	DESCRIPTION OF REVISIONS	BY	CHKD	DATE
△					△				
△					△				

APPLICABLE STANDARD				
RATING	OPERATING TEMPERATURE RANGE	-35°C TO +85°C (NOTE1)	STORAGE TEMPERATURE RANGE	-10 °C TO +60 °C
	VOLTAGE	100V AC	APPLICABLE CONTACT	—
	CURRENT	AWG28: 1 A, 30AWG: 0.5 A	APPLICABLE CONNECTOR	DF19*-14P-1H
		32AWG : 0.3 A	APPLICABLE CABLE	OUTER DIAMETER: φ 0.5 TO 0.6 mm

**SPECIFICATIONS**

ITEM	TEST METHOD	REQUIREMENTS	QT	AT
------	-------------	--------------	----	----

**CONSTRUCTION**

GENERAL EXAMINATION	VISUALLY AND BY MEASURING INSTRUMENT.	ACCORDING TO DRAWING.	○	○
MARKING	CONFIRMED VISUALLY.		○	○

**ELECTRICAL CHARACTERISTICS**

CONTACT RESISTANCE	mA (DC OR 1000 Hz).	mΩ MAX.	—	—
CONTACT RESISTANCE MILLIVOLT LEVEL METHOD	20 mV MAX, mA(DC OR 1000 Hz).	mΩ MAX.	—	—
INSULATION RESISTANCE	100V DC.	500 MΩ MIN.	○	—
VOLTAGE PROOF	300V AC FOR 1 min.	NO FLASHOVER OR BREAKDOWN.	○	—

**MECHANICAL CHARACTERISTICS**

CONTACT INSERTION AND EXTRACTION FORCES	BY STEEL GAUGE.	INSERTION FORCE EXTRACTION FORCE	N MAX. N MIN.	—	—
INSERTION AND WITHDRAWAL FORCES	MEASURED BY APPLICABLE CONNECTOR.	INSERTION FORCE EXTRACTION FORCE	N MAX. N MIN.	—	—
MECHANICAL OPERATION	TIMES INSERTIONS AND EXTRACTIONS.	①CONTACT RESISTANCE: mΩ MAX. ②NO DAMAGE, CRACK OR LOOSENESS OF PARTS.		—	—
VIBRATION	FREQUENCY 10 TO 55 Hz, SINGLE AMPLITUDE 0.75 mm, AT 2 h, FOR 3 DIRECTIONS.	①NO ELECTRICAL DISCONTINUITY OF 1 μs.		○	—
SHOCK	490 m/s <sup>2</sup> DURATION OF PULSE 11 ms AT 3 TIMES FOR 3 DIRECTIONS.	②CONTACT RESISTANCE: - mΩ MAX. ③NO DAMAGE, CRACK OR LOOSENESS OF PARTS.		○	—

**ENVIRONMENTAL CHARACTERISTICS**

RAPID CHANGE OF TEMPERATURE	TEMPERATURE -55 → 5~35 → +85 → 5~35 °C TIME 30 → 2~3 → 30 → 2~3 min UNDER 5 CYCLES.	①CONTACT RESISTANCE: 30 mΩ MAX. ②INSULATION RESISTANCE: 500 MΩ MIN. ③NO DAMAGE, CRACK OR LOOSENESS OF PARTS.		○	—
DAMP HEAT (STEADY STATE)	EXPOSED AT 40±2°C, 90~95%, 96h.	①CONTACT RESISTANCE: 30 mΩ MAX. ②INSULATION RESISTANCE: 500 MΩ MIN. ③NO DAMAGE, CRACK OR LOOSENESS OF PARTS.		○	—
RESISTANCE TO SOLDERING HEAT	SOLDER TEMPERATURE, °C, FOR IMMERSION, DURATION, s.	NO DEFORMATION ON CASE OR EXCESSIVE LOOSENESS OF THE TERMINALS.		—	—
SOLDERABILITY	SOLDERED AT SOLDER TEMPERATURE, °C FOR IN IMMERSION, DURATION, s.	SOLDER SHALL COVER A MINIMUM OF % OF THE SURFACE BEING IMMERSSED.		—	—

REMARKS	DRAWN	DESIGNED	CHECKED	APPROVED	RELEASED
NOTE 1: INCLUDE THE TEMPERATURE RISING BY CURRENT.	<i>J. Tashiro</i>	<i>J. Tashiro</i>	<i>M. Nakamura</i>	<i>K. Katayama</i>	
Unless otherwise specified, refer to MIL-STD-1344.	'98.8.4	'98.8.4	'98.8.6	'98.8.6	

Note QT:Qualification Test AT:Assurance Test ○:Applicable Test

<b>HS</b> HIROSE ELECTRIC CO., LTD.	SPECIFICATION SHEET	PART NO.	DF19-14S-1C
CODE NO.(OLD)	DRAWING NO.	CODE NO.	
CL	ELC4-162513	CL 685-0012-9	1 1

TO