## **HellermannTyton**

## **Specification Sheet**

Part Number: 166-90466



HelaGuard Non-Metallic IP66 Fitting, 90-Elbow, 2" NPT Thread, 2" Dia, PA66, Black, 2/pkg

Article Number	166-90466
Туре	HG200-90-2000
Color	Black (BK)
Features & Benefits	<ul> <li>External NPT thread provides a secure connection. Snap-on construction reduces installation time and costs by eliminating the need to thread fittings onto conduits.</li> <li>Elbow features a smooth, swept bore to ease cable installation.</li> <li>All-around "teeth" attach firmly to conduit and deliver a high extraction force.</li> <li>Durable nylon material has high resistance to salts, oils, weak acids and solvents.</li> <li>IP66 fitting has one-piece construction.</li> </ul>
Quantity Per	pack
Product Description	Elbow fitting features a snap-on design that provides a quick, secure connection. Constructed of a very durable nylon material with a high resistance to salts, oils, weak acids and solvents. Designed for easy removal with a small screwdriver. IP66 ingress protection rated fittings.

Short Description	HelaGuard Non-Metallic IP66 Fitting, 90-Elbow, 2" NPT Thread, 2" Dia, PA66, Black, 2/pkg
Global Part Name	HG200-90-2000-PA66-BK
Variant	90° Elbow
Nominal Diameter (Imperial)	2-5/8
Nominal Diameter (Metric)	67

Material	Polyamide 6.6 (PA66)
Material Shortcut	PA66
Flammability	UL 94 V2
Halogen free	Yes
Operating Temperature (Metric)	-58°F to +275°F (-50°C to +135°C)
Reach Complaint(Article 33)	Yes
ROHS Complaint	Yes
UL Recognized (US)	Yes
UL Recognized (US and Canada)	Yes

Package Quantity(Imperial)	2
Package Quantity (Metric)	2
Customs Number	3926909987

 $\ensuremath{\mathbb{C}}$  2018 HellermannTyton. All rights reserved.

Contact Us RoHS/WEEE Compliance Disclaimer Terms and Conditions