

Specification Sheet

Part Number: TSRP3FW-50



Product Description

Article Number	250-63500
Туре	TSRP3-50
Color	Office White (OEWH)
Features & Benefits	• Self-locking covers, provide taper resistant security, while the hidden positive latch permits quick re-entry access to power cables. • An integrated flexible hinge allows the raceway to endure numerous openings without stress cracking or discoloration. • Raceways and fittings are UL Listed for power up to 600 Volts and meet UL5A and CSA 22.2 Number 62-93 Standards, to insure compliance with local building codes. Raceway fittings incorporate a minimum 1" bend radius to meet TIA/EIA 568-B and 569-A standards.
Quantity Per	EA

and 5e communications systems.

HellermannTyton provides a complete line of raceway and fittings to manage connectivity requirements from the telecommunications room to the work area. Each size of raceway offers numerous fittings, offered in electrical ivory, white or office white, including TIA/EIA-568-B compliant 1" bend radius accessories which help ensure consistent data transmission performance of Category 6A, 6

Short Description	Ceiling Drop, 1-3/4", PVC, Office White, 1/bag
Global Part Name	TSRP3-50-PVC-WH
Material	Polyvinylchloride (PVC)
Material Shortcut	PVC
Halogen free	No
Reach Complaint(Article 33)	No
ROHS Complaint	Yes
Package Quantity(Imperial)	1
Package Quantity (Metric)	1
Customs Number	3925900000

Contact Us RoHS/WEEE Compliance Disclaimer Terms and Conditions

^{© 2018} HellermannTyton. All rights reserved.